
ROCK 30 FIZZ

	ROCK 30 FIZZ
Cooling capacity (l/h)	30
Max continuos supply (I)	6
Cold water temperature*	5 - 12 °C
Pump	Professional membrane carbonation pump
Cooling technology	Aluminum fusion block
Condensation	Forced ventilation
Refrigerant gas	R290
Adjustable thermostat	Yes
Supply	230 V - 50 Hz
Compressor power	1/8 HP
Absorbed power	300 W
Max. absorption	1,55 A
Working room temperature	Min 16°C - Max 32°C
Inlet water pipe	Ø5/16" (8 mm)
Inlet CO ₂ pipe	Ø5/16" (8 mm)
Dispensing area height (mm)	274
Туроюду	Countertop
Net weight (kg)	28
Gross weight (kg)	31
Dimensions W x D x H (mm)	261 x 498 x 418
Packaging dimensions (mm)	350 x 580 x 510
Dispensing options	Cold still water, cold sparkling water and room temperature water
Materials	Parts in robust stainless steel and ABS plastic
Push buttons	Stainless steel push buttons
Alarms	No water, no Co2





OTHER CHARACTERISTICS

Drip tray prepared for drainage

OPTIONAL

Water pressure reducer

CO₂ pressure reducer

Filters

UV LED OUT, BLUFIRE or NANO SILVER PIPE

Cabinet

BLUSODA CABINET in stainless steel

* rated at a room temp. of 25 °C and inlet water temp. of 20 °C The image contained in this datasheet may not correspond to reality

CERTIFICATIONS

C E DM 174/04



 \mathbf{O}

30 It/h

I.T.

DRY

GAS R290

fizz •



BLUPURA USA INC. - USA | Phone +1 305 777 3591 blupurausa@blupura.com | www.blupura.com

BLUPURA SRL - Italy | Tel. +39 071 971 0080 info@blupura.com | www.blupura.com